

Capiphon Installation Tools List

WHAT	YES/NO
Tape measure	
Scissors or sharp knife to cut belt to length. An A4 stationery guillotine is handy for large jobs.	
Capiphon Belt. <ul style="list-style-type: none"> • Capiphon is sold as 10m rolls of 100mm wide belt specifically for inserting into collector pipe. • Capiphon is also sold as 5.8m rolls of 175mm wide for wrapping around 50mm DWV to create the Capiphon Pipe. 	
Collector pipe – 50mm DWV is best for areas under traffic.	
Angle grinder to cut slots in discharge pipe. Use 2mm or 3mm wheel.	
Silicone sealant or waterproofing tape to seal end of belt, and to seal insertion slot. Most sealants are OK, but the ordinary kitchen/bathroom variety is best – it is not too sticky and yet remains flexible for a while before firming up.	
Cable ties (300mm) to hold belt into discharge pipe slot while placing into trench	
Heat gun, Esky and hot water bottles for cold areas/days.	
Coarse sand. DO NOT USE FAT SAND. See WHAT SAND TO USE? - A Simple Permeability Test	
Drill or angle grinder to cut slot into sump pit wall	
Ditto jig saw	
Spade	
Capiphon Pipe if required. Capiphon is sold as 5.8m of 175mm wide belt specifically to wrap around 50mm DWV. This is best done in a clean workshop or other suitable area such as a basement in a new building.	